



To reduce the risk of fire and electrocution, please refer to a certified electrician for installation of the EVSE.

WARNING! Disconnect electrical power to the Revitalize Charging Solutions Level 2 Charging Station before installation. Failure to do so may cause physical injury or damage to the electrical system and charging unit.

50A - 240V Dual Port

Tools Required: Drill, Stud Finder, Screwdriver, and Level

P
A
R
T
S

WALL BRACKET



1A

EV CHARGER



2

ENCLOSURE SCREW



2A

CABLE HOLDER



3

J1772 CABLE



4

I
N
S
T
R
U
C
T
I
O
N
S



1

Using a stud finder, locate the center of stud for mounting of charger wall



1A

Mount wall bracket with the provided screws using a drill or screwdriver.



2

NEMA 14-50 Plug Installation (Inside-use Only)

Remove electrical cover using a Phillips screwdriver.


Knockout the hole at the bottom of the power panel.

Insert conduit or power wire through the hole and terminate electrical wires to L1/ L2/ PE and secure power door.



2A

Insert the REV+ Dual Home Charger into the mounted wall bracket using the provided screws.



3

Mount cable holder to the wall using two (2) provided 1/2 inch screws.



4

Second port J1772 cable connect to inlet at the bottom of the charger

For the steps for Hard Wire Installation, go to the [user manual](#).